



BEARING BOWER CORP.

20,000 mm x 47,000 mm x 31 mm
15UZ21006T2 Eccentric Bearing



Bearing No. UC204D1

UC204D1 Bearing 2D drawings and 3D CAD models

Size	20x47x31 mm
Bore Diameter	20,000 mm
Outer Diameter	47,000 mm
Width	31 mm
d	20,000 mm
D	47,000 mm
B	31 mm
C	17 mm
Category	Insert Bearings Spherical OD
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.165
EAN	4547359231465
Product Group	M06110
Inner Race Profile	Wide Inner Ring
Outer Race Profile	Spherical
Relubricatable	Yes
Seal Type	Single Lip Land Riding
Mounting Method	Set Screw
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	20MM Bore; Wide Inner Ring; Ball Bearing; 31MM Length Thru Bore; 17MM Outer Race Width; 47MM



BEARING BOWER CORP.

	Outside Diameter; Relubricatable; Single Lip Land Riding Seal; Set Screw Mounting Method; No Snap Ring
Inch - Metric	Metric
Other Features	Single Row Light Duty Steel Cage Has Flinger Metric
Category	Insert Bearings
UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	UC204D1
Weight / LBS	0.375
Outer Race Width	0.669 Inch 17 Millimeter
Bore	0.787 Inch 20 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Length Thru Bore	1.22 Inch 31 Millimeter
bore diameter:	20 mm
fillet radius:	1 mm
outside diameter:	47 mm
radial dynamic load capacity:	12800 N
outer ring width:	17 mm
radial static load capacity:	6650 N
inner ring width:	31 mm
bearing material:	Through Hardened Steel
bore type:	Round
finish/coating:	Uncoated
locking device:	Set Screw Collar
maximum rpm:	6700 RPM



BEARING BOWER CORP.

duty type:	Standard Duty
seal type:	Contact
overall width:	31 mm
series:	UC2
operating temperature range:	-40 to 120 ° C
manufacturer product page:	Click here